

INSTRUCTIONS FOR USE



Lift up the headrest without removing it and attach ad'just® using the Velcro strip.

Position the air pump within arm's reach so that it does not interfere with driving or with safety installations such as the seatbelt or airbag. Shorten the rubber tube if necessary.





Feed the bottom of ad'just® through the gap between the base and the back of the seat

To avoid possible discomfort, position the side cushions so that they do not exert continual pressure on your body. The support they offer will become apparent when taking corners.

A few tips:

Perfect adjustment is rarely achieved straight away. You may need to try a few times before finding the right position.

A good piece of advice: Adapt ad'just® to your needs! Some users often inflate and deflate the cushion, others place it at the bottom of the seat or even vertically...

Warning! This product is only designed for adults and children over the age of 10. Under no circumstances can it be a substitute for an approved child seat.



warranty@adjust.fr





You will need to be seated to adjust the height of the inflatable lumbar support cushion. Slip your hand between the back of the seat and ad'just® and peel off the cushion. Slide it down to the lumbar region of your back and remove your hand when it seems to be most comfortable for you.

adjust

MONOBLOC KI

adjust

CUSHION SEAT

The cushion will remain fixed in this position.



Kit for assembling the lumbar support cushion on a monobloc seat

SEAT CUSHION

Adjust the angle of the back / leg base to alleviate tension





adjust sas : 92 route de Jallieu | 38080 Saint Marcel Bel Accueil | France

® Patent and registered trademark

adjust

LUMBAR SUPPORT CUSHION